

Test Certificate

Nº: CYL0008/2020

Tested by request of:

**Sanko Tekstil İşletmeleri San. ve
Tic. A.Ş. ISKO Şubesi**

Manufacturer

Sanko Tekstil İşletmeleri San. ve Tic. A.Ş. ISKO Şubesi

Organize Sanayi Bölgesi 3. Cadde 16400

16400 İnegöl-BURSA

Turkey

Product Information

FACE COVER 871176 (33B)

Reusable 30 times

Adult Size

Washing 60°C; flat drying

The sample(s) has been tested at Eurofins Laboratories and found to be in conformity with:

“CWA 17553:2020 Community face coverings - Guide to minimum requirements, methods of testing and use”

As can be found in the test report (s):

- AR-20-YL-005182-01
- AR-20-YL-006868-01
- AAJ40787
- CH_IKT_2

And reached the classification of **Level 70%** for material filtration efficiency test.

Signed on behalf of Eurofins Textile Testing Spain S.L.U by:

Luis Miralles Esteve

Quality Manager

Test Certificate

Nº: CYL0008/2020

SUMMARY OF RESULTS

Requirements, methods of testing and use CWA 17553:2020

Section	Test	Result
5.2	Visual inspection	PASS
5.4	Packaging	PASS
5.6	Cleaning	PASS
5.7	Surface condition of the parts (as received)	PASS
5.7	Surface condition of the parts (after 30 washing cycles)	PASS
5.9 & 6.3	Head harness (as received)	PASS
5.9 & 6.3	Head harness (after 30 washing cycles)	PASS
5.3	Dimensions / Sizing	PASS
5.3.1	Adult sizing (as received)	PASS
5.3.1	Adult sizing Head harness (after 30 washing cycles)	PASS
5.3.2	Child sizing	NOT APPLICABLE
	Performance	PASS
5.8	Material filtration efficiency test	LEVEL 70%
	Bacterial Filtration Efficiency (as received) ¹	86,06%
	Bacterial Filtration Efficiency (after 30 washing cycles) ¹	85,04%
	Particle filter penetration (as received) ²	99%
	Particle filter penetration (after 30 washing cycles) ²	94%
5.10	Breathing resistance (as received) ³	62.8 Pa/cm ² - PASS
5.10	Breathing resistance (after 30 washing cycles washing) ³	44.0 Pa/cm ² - PASS
7	Marking and instructions for use	PASS
7.1	Marking	PASS
7.2	Instructions for use	PASS

¹ Tested according to EN 14683 Annex B

² Tested according to EN 13274-7

³ Tested according to EN 14683 Annex C

End of document